

Für Serie »speedfit« und »sharbite«

Zur Wandbefestigung der starren PA- oder Alu-Rohre.

Material Polypropylen (PP)
 Betriebstemperatur -20 bis 65 °C



88.015-S

Rohrklemme, farbig

Artikel Nr.	Typen Nr.	für Rohr-Außen- \emptyset mm	Farbe	A mm	B mm
114035	88.015-S	15	schwarz	19,5	25,0
114036	88.018-S	18	schwarz	21,2	29,0
114037	88.022-S	22	schwarz	23,0	35,0
114038	88.028-S	28	schwarz	26,0	43,0
117067	RHKL3538	35 - 40	schwarz	-	-
117068	RHKL4044	40 - 44	schwarz	-	-
117069	RHKL4854	48 - 54	schwarz	-	-
114039	88.015-B	15	blau	19,5	25,0
114040	88.018-B	18	blau	21,2	29,0
114041	88.022-B	22	blau	23,0	35,0
114042	88.028-B	28	blau	26,0	43,0
114043	88.015-R	15	rot	19,5	25,0
114044	88.018-R	18	rot	21,2	29,0
114045	88.022-R	22	rot	23,0	35,0
114046	88.028-R	28	rot	26,0	43,0
114047	88.015-W	15	weiß	19,5	25,0
114048	88.018-W	18	weiß	21,2	29,0
114049	88.022-W	22	weiß	23,0	35,0
114050	88.028-W	28	weiß	26,0	43,0



RHKL4854



88.015-B



88.015-R



88.015-W

